

TECHNICAL DATA SHEET

eme GANTRY Cranes

MODEL	WLL	PLA	Standard Beam	Beam Length	Minimum Height To Lift Ring	Maximum Height To Lift Ring	Standard Caster Size	Leg Span	Assembled Weight	Height Hole Space
	(lb)	(lb)	(ft)	(ft)	(in)	(in)	(in)	(in)	(lb)	(in)
1100R	1100	1650	8	6 - 30	66	90	6	48	155	6
1650R	1650	2475	10	6 - 25	66	90	6	48	165	6
2200R	2200	3300	8	6 - 20	66	90	6	48	165	6
2200LW	2200	3300	10	6 - 20	90	122	6	63	195	8
2200HD	2200	3300	12	6 - 20	90	122	6	63	215	8
4400M	4400	6600	8	6 - 15	66	90	6	48	165	6
4400R	4400	6600	15	6 - 15	95	135	6 or 8*	66	295	8
6600R	6600	9900	15	6 - 15	106	154	8	70	525	8
8800R	8800	13200	12	6 - 12	110	150	8	83	545	10
11000R	11000	14300	10	6 - 10	110	150	8	83	545	10

*6 in. casters Standard on 4400R; Upgrade to 8 in. available.

Beam Adjustment Hole Spacing: 8 in. on all beam lengths

Clear Span for beam is 3 ft. less than beam length

Custom Height GANTRY Cranes available.

Contact eme at 1-888-679-5283 for current information.