



**LIFT IT...MOVE IT...SAFELY!**

PRO SERIES	LIFT CAP (lb)	PROOF LOAD (lb)	LIFT RANGE (in)	MAX ASSEMBLED HEIGHT (in)	STD BEAM LENGTH (ft)	MAX BEAM LENGTH (ft)	HEIGHT ADJUST (in)	CASTER SPREAD (in)	ASSEMBLED WEIGHT (lb)
1100R	1100	1650	66-90	105	8	30	6	48	260
2200R	2200	3300	66-90	105	8	26	6	48	270
2200LW	2200	3300	82-122	138	10	26	8	65	300
4400M	4400	6600	66-90	105	10	15	6	48	290
4400R	4400	6600	82-122	138	10	15	8	65	350
4400T	4400	6600	98-138	153	15	15	8	65	380
6600R	6600	9900	106-154	178	15	16.5	8	73	585
11000R	11000	16500	106-154	178	15	16.5	8	73	715
16500R	16500	20625	97-139	173	15	15	7	81	955
20000R	20000	25000	97-139	169	15	15	7	81	975

Beam Clear Span: 3 ft. less than Beam length    Distance Between Casters: 1 foot less than Beam length  
 Custom 2200XT and 4400XT Models Available. Contact eme for specs and pricing

- Documentation Supplied with each eme Gantry and Davit Crane**
1. Engineer's Stamped Drawing
  2. Signed Certificate of Test (crane tested to Proof Load)
  3. Operator's Manual
  4. 10 Year Warranty against Manufacturer's Defects

All welding on Gantry and Davit Cranes, Sockets performed by certified shop  
 Struts and Leg Extrusions matched to Gantry Capacity and Lift Height  
 Locking 'Surround-Beam' Trolley is Standard with all **eme** Gantry Cranes  
 All Gantry Cranes Proof Tested to 125 to 150% of Rated Capacity before shipment to customer  
 Locking Casters (independently for swivel, roll) Gantry can be rolled when loaded  
 Gr. L9 Chromate Plated Fasteners. Bolted Assembly is the stronger assembly than with pins  
 North American made; North American parts; built for North American conditions  
 All Gantry Cranes can be assembled from the Ground Up with 1-4 people  
 Two wrenches only tools needed to assemble any **eme** Gantry Crane  
 Extruded engineered hollow Box-Beams stronger and lighter than steel 'I' beams

**Contact eme at 888-679-5283 for current information, pricing, parts**  
**For Parts: parts@easilymovedequipment.com**